



L-BOXX 65B from plastic with standard equipment for electrical installations



↪ Comprehensive equipment for conductor preparation, comprising cable cutter, cable knife, crimping tool and connectors

Characteristics

- Manufactured from shock and impact resistant ABS plastic, very robust, 100 kg capacity
- Stackable using an Easy-Click system, which allows easy opening and closing

Item	Dimensionmm	Part No.
L-BOXX from plastic with standard equipment for electrical installations	442 x 357 x 117	LBOXX65B

Scope of supply	Description	Quantity	Page
K05	Crimping tool for tubular cable lugs and connectors, standard type 6 - 50 mm ²	1	229
K100	Hand-operated cutting tool for Cu and Al cables to 14 mm dia.	1	348
KL740416	Cable knife, without blade 4 - 16 mm dia.	1	528
1R6	Tubular cable lug without inspection hole, 6 mm ² , M6, Cu tinned	25	14
1R8	Tubular cable lug without inspection hole, 6 mm ² , M8, Cu tinned	25	14
2R6	Tubular cable lug without inspection hole, 10 mm ² , M6, Cu tinned	25	14
2R8	Tubular cable lug without inspection hole, 10 mm ² , M8, Cu tinned	25	14
3R10	Tubular cable lug without inspection hole, 16 mm ² , M10, Cu tinned	25	14
4R8	Tubular cable lug without inspection hole, 25 mm ² , M8, Cu tinned	20	14
4R10	Tubular cable lug without inspection hole, 25 mm ² , M10, Cu tinned	20	14
5R8	Tubular cable lug without inspection hole, 35 mm ² , M8, Cu tinned	20	14
5R10	Tubular cable lug without inspection hole, 35 mm ² , M10, Cu tinned	20	14
6R10	Tubular cable lug without inspection hole, 50 mm ² , M10, Cu tinned	15	15
LBOXX102LFGL-BOXX with front handle		1	

L-BOXX with electromechanical crimping tool EK 50 ML 0.14 to 50 mm² and extensive additional equipment

Item	Dimensionmm	Part No.
L-BOXX with electromechanical crimping tool EK 50 ML 0.14 - 50 mm ² and extensive additional equipment	442 x 357 x 151	LBOXXEK50ML

Scope of supply	Description	Quantity	Page
RAML1	Battery 10.8 V / 1.5 Ah, Li-Ion (16.2 Wh)	1	485
LGML1	Charger for 10.8 V Li-Ion batteries, 230 V	1	487
K118	Hand-operated cutting tool for Cu and Al cables to 12 mm dia.	1	348
AE502	Crimping dies AE 50, 10 - 25 mm ²	1	312
47612	Insl. cable end-sleeve, 10 mm ² , 22 mm	50	139
47712	Insl. cable end-sleeve, 16 mm ² , 24 mm	50	140
47818	Insl. cable end-sleeve DIN 46228 part 4, 25 mm ²	25	140
R505	Crimping dies R 50, 16 - 25 mm ²	1	312
3R8	Tubular cable lug without inspection hole, 16 mm ² , M8, Cu tinned	25	14
4R8	Tubular cable lug without inspection hole, 25 mm ² , M8, Cu tinned	25	14
AE503	Crimping dies AE 50, 35 - 50 mm ²	1	312
47918	Insl. cable end-sleeve DIN 46228 part 4, 35 mm ²	25	140
48025	Insl. cable end-sleeve DIN 46228 part 4, 50 mm ² , 40 mm long	20	140
IS5072	Crimping dies IS 50, single crimping, 10 - 16 mm ²	1	313
652C6	Insl. solderless terminal M6, 10 mm ² , fork-type	50	80
LBOXX136LFGL-BOXX with front handle (W/D/H: 442 x 357 x 151 mm)		1	