## EKM 60/22 Battery powered hydraulic crimping tool 6 - 300 mm<sup>2</sup>











←Large crimping range up to 300 mm<sup>2</sup> ←All tool data in view thanks to display and i-press app

## Characteristics

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Closed head, flip top style, rotatable
- Quality assurance via visual and audible signals in case of error
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- Simple and safe: Automatic retraction when operation is complete
- Automatic retract stop (ARS) for positioning control in case of multiple crimps
- Always ready-to-use thanks to battery charge and service display

## Suitable for

22-series interchangeable dies, narrow crimping

Technical data					
Crimping force	60 kN				
Hub	17.5 mm				
Crimping range	6 - 300 mm <sup>2</sup>				
Crimping cycle	2 s (bei ARS) und 5 s (depending on crimp cross-section)				
Charging time	15 min.				
Weight incl. battery	3.0 kg				
Ambient temperature	-10 °C up to +-	40°C			
Item			Part NoBosch	Part NoMakita	
Battery powered hydraulic cr	imping tool 6 -	300 m	mERM6022CFB	EKM6022CFM	
Scope of supply					Page
Bosch battery 18 V / 2.0 Ah, Li-lon		RALB1EU		484	
Bosch quick-charger for 18 V Li-lon battery		LGLB1EU		486	
Plastic case			KK50NG		
Makita battery 18 V / 1.5 Ah, Li-lon				RAL1	483
Makita quick-charger for 18 V Li-lon battery				LGL1	486
Plastic case				KK50L	
Accessories					Page
Bosch battery 18 V / 5.0 Ah, Li-lon		RALB2EU		485	
Makita battery 18 V / 4.0 Ah, Li-lon			RAL40	484	
Variants					Page
L-BOXX with battery powered EKM6022CFB, 6 - 300 mm <sup>2</sup>	d crimping tool	1	LBOXXEKM6022CF	-B	203
L-BOXX with battery powered crimping tool LBOXXEKM6022 EKM6022CFM, 6 - 300 mm <sup>2</sup>					M 203