Battery powered hydraulic cutting tool with remote control 20 mm

and 32 mm dia.









Scope of supply for ES 20 RMC

- ⇐Tool with remote control, e.g. for telescopic rods
- ←ES20RMC: For cutting Al/St conductors (ACSR) to DIN EN 50182, solid Al/Cu cables to DIN EN 60228, Class 1 and laminated copper bus bars
- ⇐ES32RMC: Cuts multi-stranded Al/Cu cables Class 2
- ⇐Extremely robust design and lightweight
- ⇔Slim cutting head ideal when space is critical
- ←All tool data in view thanks to display and i-press app
- ⇔Powerful 18 V Li-Ion battery high capacity, short charging time
- ←Can also be used as a normal cable cutter when the Hotstick holder is not attached

Characteristics

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Open head, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless operations due to balanced centre of gravity, even when used with a telescopic rod
- LED for work area illumination
- Quick motor stop for high user safety
- Simple and safe: Automatic retraction when operation is complete
- Manual retract stop (MRS) for efficient operations
- Energy saving: Motor stops when the operation is complete
- Always ready-to-use thanks to battery charge and service display
- Simple one-hand operation via remote control

ES 20 RMC suitable for

- Al/St wire (ACSR)
- Solid Al/Cu cables to DIN EN 60228 Class 1
- Laminated Cu bus-bars

ES 32 RMC suitable for

Multi-stranded Al/Cu cable Class 2

Additional information

Part number suffix for tools without battery and charger "0000"

Technical data				
Head type	Cutter open			
Cutting range	max. Ø 20 mm / max. Ø 32 mm			
Cutting time	2 s to 8 s (depending on material thickness)			
Charging time	15 min.			
Weight incl. battery	2.0 kg			
Ambient temperature	-10 °C up to +40 °C			
Item		Part NoBosch	Part NoMakita	
Battery powered hydraulic cu	ıtting tool 20 mm dia.	ES20RMCCFB		
Battery powered hydraulic cutting tool 20 mm dia.			ES20RMCCFM	
Battery powered hydraulic cutting tool 32 mm dia. ES32RMCCFB				
Battery powered hydraulic cutting tool 32 mm dia.			ES32RMCCFM	
Scope of supply				Page
Bosch battery 18 V / 2.0 Ah, Li-Ion		RALB1EU		484
Makita battery 18 V / 1.5 Ah, Li-lon			RAL1	483
Bosch quick-charger for 18 V Li-lon battery		LGLB1EU		486
Makita quick-charger for 18 V Li-lon battery			LGL1	486
Bluetooth remote control		BTC2	BTC2	
Accessories				Page
Bosch battery 18 V / 4.0 Ah, Li-lon		RALB2EU		485
Makita battery 18 V / 4.0 Ah, Li-Ion			RAL40	484
Replacement blade set fEss 20 RMC		ES20E	ES20E	
Replacement blade set f65 32 RMC		ES32E	ES32E	