

ES 65 Battery powered hydraulic cutting tool 65 mm dia.



- ↪ Cuts copper and aluminium cables with lightweight steel armouring (depending on cable type)
- ↪ Also suitable for fine-stranded cables (depending on cable type)
- ↪ Saves time with multiple cuts thanks to innovative opening mechanism
- ↪ All tool data in view thanks to display and i-press app

Characteristics

- All data can be easily read via Bluetooth
- Choose your battery system: Bosch or Makita
- Open head, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- 2-stage hydraulic system with fast feed and power stroke
- Simple and safe: Automatic retraction when operation is complete
- Manual retract stop (MRS) for efficient operations
- Always ready-to-use thanks to battery charge and service display

Suitable for

- Cu/Al cable

Technical data

| | |
|----------------------|---------------------------------|
| Head type | Cutter open |
| Cutting range | max. 65 mm dia. |
| Cutting force | 40 kN |
| Cutting time | Depending on material thickness |
| Charging time | 45 min. |
| Weight incl. battery | 6.3 kg |
| Ambient temperature | -12 °C up to +40°C |

| Item | Part NoBosch | Part NoMakita | |
|---|--------------|---------------|------|
| Battery powered hydraulic cutting tool 65 mm dia. | ES65CFB | ES65CFM | |
| Scope of supply | | | Page |
| Bosch battery 18 V / 5.0 Ah, Li-Ion | RALB2EU | | 485 |
| Bosch quick-charger for 18 V Li-Ion battery | LGLB1EU | | 486 |
| Makita battery 18 V / 3.0 Ah, Li-Ion (54 Wh) | | RAL2 | 483 |
| Makita quick-charger for 18 V Li-Ion battery | | LGL1 | 486 |
| Plastic case 450 x 370 x 105 mm | KK120NG | KK120NG | |
| Accessories | | | Page |
| Replacement blade | ES65E | | |
| Bosch battery 18 V / 5.0 Ah, Li-Ion | RALB2EU | | 485 |
| Makita battery 18 V / 4.0 Ah, Li-Ion | | RAL40 | 484 |