

SAFETY CUTTER

Tested and certified according to GS-ET-23

NEW



SC105M / SC85M

Battery hydraulic safety cutting tool with remote control, Ø 105 mm / Ø 85 mm, with 18 V Makita battery



SC105B / SC85B

Battery hydraulic safety cutting tool with remote control, Ø 105 mm / Ø 85 mm, with 18 V Bosch battery



**REED SENSOR FOR
RELIABLE CUT
DETECTION**

**TESTED AND CERTIFIED
ACCORDING TO GS-ET-23**



**UNIQUE BLUETOOTH
DISTANCE MEASUREMENT
(UP TO MAX. 50 M)**

**SC105M/B
SC85M/B**



**FOR MORE KLAUKE
UTILITY PRODUCTS:**



IEC International
Electrotechnical
Commission



LONG RANGE:
Connection status visualised
via remote control



BATTERY STATUS MONITORING:
100% prevention of incomplete cuts



SPACE-SAVING:
Lightweight and compact
design



LOW MAINTENANCE:
No regular oil and
hose changes necessary

TECHNICAL DETAILS

	SC105M/B	SC85M/B
Area of application	- Multi-core cables up to 60 kV - Single-core cables up to 110 kV	- Multi-core cables up to 60 kV - Single-core cables up to 110 kV
Cutting range	Ø 105 mm	Ø 85 mm
Low voltage	e.g. NYCWY and NAYY up to 4x300 mm ²	e.g. NYCWY and NAYY up to 4x300 mm ²
Medium voltage	e.g. NKBA 3x300 mm ² (6/10 kV) NA2XS2Y 3x1x500 mm ² (20 kV)	e.g. NKBA 3x300 mm ² (6/10 kV) NA2XS2Y 3x1x240 mm ² (20 kV)
Weight with battery	10,5 kg	6,9 kg
Protection class	IP 55	IP 55

Klauke®

Gustav Klauke GmbH
Auf dem Knapp 46
D-42855 Remscheid

Tel.: +49 (0) 2191 / 907 - 0
Klauke-Info@Emerson.com
www.klauke.com


EMERSON™